



LOAD IT UP

Improve the productivity of your compact tractor with a new Massey Ferguson front loader.



Our new high-performance loaders for Massey Ferguson sub-compact and compact tractors are designed to get more work done with less. In addition to high lift capacity, we have optimized loader efficiency with fast cycle times and protected hydraulic lines by routing them inside the loader frame. From streamlined functionality to smart details, Massey Ferguson front loaders offer a unique combination of design, performance, and affordability.

- Loader frames feature a tapered design and low mount cross-tube that provides excellent lateral field of vision and unobstructed view for connecting/disconnecting implements.
- Positive locking galvanized pins at all hinges eliminate rotation that can lead to wear and feature integrated, recessed grease zerks to protect against accidental damage.
- Quick-detach loader frame with built-in stands for speedy loader removal and attachment without the need for tools.



Models Available

LOADER MODEL	CONFIGURATION	COMPATIBLE TRACTOR MODEL
DL95	Non-self leveling (NSL)	GC1700 Series
L105E	Non-self leveling (NSL)	1726E, 1734E, 1739E
DL125	Non-self leveling (NSL)	1736, 1742
DL135	Non-self leveling (NSL)	1749, 1754, 1758, 1759

Specifications

LOADER MODEL	DL95	L105E	DL125	DL135
Lift capacity to max. height lbs. (kg)*	580 (270)	830 (380)	1,300 (590)	1,760 (800)
Breakout force lbs. (kg)*	920 (420)	1,460 (660)	2,190 (990)	2,860 (1,300)
Max. lift height in. (mm) measured at pivot	72.8 (1,850)	95.7 (2,400)	102.4 (2,600)	110.2 (2,800)
Max. dump angle	50 degrees	45 degrees	48 degrees	48 degrees
Max. rollback angle	25 degrees	25 degrees	45 degrees	45 degrees
Max. rollback force lbs. (kg)	2,120 (960)	3,260 (1,480)	3,160 (1,430)	4,140 (1,880)
Digging depth in. (mm)	2.8 (70)	3.2 (80)	3.5 (90)	5.4 (140)
Tool attachment	Pin Type	Pin type or skid steer quick attachment		

* Measured 31.5" forward of pivot

All specifications indicated are manufacture's estimates and subject to change without notice.

